

EXHIBIT D



US010491982B1

(12) **United States Patent**
Koss et al.

(10) **Patent No.:** **US 10,491,982 B1**

(45) **Date of Patent:** ***Nov. 26, 2019**

(54) **SYSTEM WITH WIRELESS EARPHONES**

(56) **References Cited**

(71) Applicant: **Koss Corporation**, Milwaukee, WI (US)

U.S. PATENT DOCUMENTS

5,784,685 A 7/1998 Stanford et al.

6,006,115 A 12/1999 Wingate

(Continued)

(72) Inventors: **Michael J. Koss**, Milwaukee, WI (US); **Michael J. Pelland**, Princeton, WI (US); **Michael Sagan**, Fairfield, CA (US); **Steven R. Reckamp**, Crystal Lake, IL (US); **Gregory J. Hallingstad**, Deforest, WI (US); **Jeffery K. Bovee**, Sterling, IL (US); **Morgan J. Lowery**, Deforest, WI (US)

FOREIGN PATENT DOCUMENTS

JP 2004-320597 11/2004

JP 2008-67258 A 3/2008

(Continued)

(73) Assignee: **KOSS CORPORATION**, Milwaukee, WI (US)

OTHER PUBLICATIONS

Supplementary European Search Report for European Application No. 09731146.8 dated Jun. 10, 2011, 7 pages.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

Primary Examiner — Kiet M Doan

(74) *Attorney, Agent, or Firm* — K&L Gates LLP

(21) Appl. No.: **16/528,701**

(22) Filed: **Aug. 1, 2019**

Related U.S. Application Data

(63) Continuation of application No. 16/375,879, filed on Apr. 5, 2019, which is a continuation of application (Continued)

(51) **Int. Cl.**
H04R 3/00 (2006.01)
H04R 1/10 (2006.01)

(Continued)


(52) **U.S. Cl.**
CPC **H04R 1/1041** (2013.01); **H03G 3/02** (2013.01); **H03K 17/9622** (2013.01); (Continued)

(58) **Field of Classification Search**
CPC ... H04R 1/1016; H04R 25/554; H04R 1/1008 (Continued)

(57) **ABSTRACT**

Apparatus comprises adapter and speaker system. Adapter is configured to plug into port of personal digital audio player. Speaker system is in communication with adapter, and comprises multiple acoustic transducers, programmable processor circuit, and wireless communication circuit. In first operational mode, processor circuit receives, via adapter, and processes digital audio content from personal digital audio player into which adapter is plugged, and the multiple acoustic transducers output the received audio content from the personal digital audio player. In second operational mode, wireless communication circuit receives digital audio content from a remote digital audio source over a wireless network, processor circuit processes the digital audio content received from remote digital audio source, and the multiple acoustic transducers output the audio content received from the remote digital audio source.

20 Claims, 16 Drawing Sheets



US 10,491,982 B1

Page 2

Related U.S. Application Data

No. 16/182,927, filed on Nov. 7, 2018, now Pat. No. 10,368,155, which is a continuation of application No. 15/962,305, filed on Apr. 25, 2018, now Pat. No. 10,206,025, which is a continuation of application No. 15/650,362, filed on Jul. 14, 2017, now Pat. No. 9,986,325, which is a continuation of application No. 15/293,785, filed on Oct. 14, 2016, now Pat. No. 9,729,959, which is a continuation of application No. 15/082,040, filed on Mar. 28, 2016, now Pat. No. 9,497,535, which is a continuation of application No. 14/695,696, filed on Apr. 24, 2015, now Pat. No. 9,438,987, which is a continuation of application No. 13/609,409, filed on Sep. 11, 2012, now Pat. No. 9,049,502, which is a continuation of application No. 13/459,291, filed on Apr. 30, 2012, now Pat. No. 8,571,544, which is a continuation of application No. 12/936,488, filed as application No. PCT/US2009/039754 on Apr. 7, 2009, now Pat. No. 8,190,203.	7,099,370 B2 7,120,388 B2 7,139,585 B2 7,266,390 B2 7,337,027 B2 7,467,021 B2 7,512,414 B2 7,599,679 B2 7,650,168 B2 7,680,490 B2 7,697,899 B2 7,734,055 B2 7,764,775 B2 7,805,210 B2 7,861,312 B2 7,962,482 B2 8,023,663 B2 8,027,638 B2 8,055,007 B2 8,073,137 B2 8,086,281 B2 8,102,836 B2 8,190,203 B2 8,295,516 B2 8,335,312 B2 8,401,202 B2 8,478,880 B2 8,483,755 B2 8,553,865 B2 8,571,544 B2 8,655,420 B1 8,792,945 B2 9,049,502 B2 9,497,535 B1 9,729,959 B2 2003/0182003 A1 2004/0107271 A1 2005/0064853 A1 2005/0136839 A1 2005/0198233 A1 2006/0083388 A1 2006/0206487 A1 2006/0212442 A1 2006/0212444 A1 2006/0238878 A1 2006/0268830 A1 2007/0008984 A1 2007/0037615 A1 *	8/2006 10/2006 11/2006 9/2007 2/2008 12/2008 3/2009 10/2009 1/2010 3/2010 4/2010 6/2010 7/2010 9/2010 12/2010 6/2011 9/2011 9/2011 11/2011 12/2011 12/2011 1/2012 5/2012 10/2012 12/2012 3/2013 7/2013 7/2013 10/2013 10/2013 2/2014 7/2014 6/2015 11/2016 8/2017 9/2003 6/2004 3/2005 6/2005 9/2005 4/2006 9/2006 9/2006 9/2006 10/2006 11/2006 1/2007 2/2007 3/2007 3/2007 6/2007 7/2007 11/2007 12/2007 1/2008 2/2008 3/2008 3/2008 8/2008 9/2008 9/2008 10/2008 12/2008 12/2008 1/2009 5/2009 5/2009 10/2009 11/2010 11/2011 2/2013 4/2013 8/2015 11/2017	Takahashi Hall Hachimura et al. Mathews Nishiguchi et al. Yuen Jannard et al. Awiszus Bailey Bloebaum et al. Rofougaran Chiloyan Tarkoff et al. Cucos Lee et al. Handman Goldberg Sanguino Kim Weinans et al. Rabun et al. Jerlhagen Pelland et al. Kondo et al. Gerhardt et al. Brooking Finkelstein et al. Kumar Menard et al. Pelland et al. Pelland et al. Russell et al. Pelland et al. Koss et al. Koss et al. Takashima Ahn et al. Radpour Seshadri et al. Manchester Rothschild Harada Conrad Handman et al. Miyake Evans Phillips Glezerman H04M 1/6066 455/575.2 Walsh et al. Lee Rezvani et al. Rezvani Kimura et al. Nurmi et al. Bevirt et al. Angelhag Van Horn Rosener H04M 1/6066 455/575.2 Haupt et al. Richenstein et al. Rutschman Paulson et al. Johnson H04R 1/1091 381/74 Hansen et al. Lair et al. Bevirt et al. Camp et al. Paulson et al. Haseagawa Goldman et al. Pelland et al. Moriya et al. Koss et al. Koss et al.
(60) Provisional application No. 61/123,265, filed on Apr. 7, 2008.			
(51) Int. Cl.			
H04W 48/20 (2009.01)			
H04M 1/02 (2006.01)			
H04R 5/033 (2006.01)			
H04R 5/04 (2006.01)			
H03G 3/02 (2006.01)			
H04R 1/02 (2006.01)			
H04L 29/12 (2006.01)			
H04H 20/95 (2008.01)			
H03K 17/96 (2006.01)			
H04W 4/80 (2018.01)			
H04W 84/12 (2009.01)			
H04W 84/18 (2009.01)			
H04R 25/00 (2006.01)			
(52) U.S. Cl.			
CPC H04H 20/95 (2013.01); H04L 61/6068 (2013.01); H04M 1/0254 (2013.01); H04R 1/02 (2013.01); H04R 1/1091 (2013.01); H04R 3/00 (2013.01); H04R 5/033 (2013.01); H04R 5/04 (2013.01); H04W 4/80 (2018.02); H04W 48/20 (2013.01); H03K 2217/960785 (2013.01); H04R 25/554 (2013.01); H04R 2201/103 (2013.01); H04R 2201/107 (2013.01); H04R 2225/55 (2013.01); H04R 2420/07 (2013.01); H04W 84/12 (2013.01); H04W 84/18 (2013.01)	2007/0049198 A1 2007/0053543 A1 2007/0136446 A1 2007/0165875 A1 2007/0253603 A1 2007/0297618 A1 2008/0019557 A1 2008/0031470 A1 2008/0062939 A1 2008/0076489 A1 *	3/2007 3/2007 6/2007 7/2007 11/2007 12/2007 1/2008 2/2008 3/2008 3/2008	
(58) Field of Classification Search			
USPC 381/74, 77, 386, 71.6, 381, 59, 306, 309, 381/103; 455/556.1, 462, 66.1, 575.2, 455/41.2; 370/412, 338	2008/0194209 A1 2008/0215777 A1 2008/0226094 A1 2008/0242312 A1 2008/0298606 A1 *	8/2008 9/2008 9/2008 10/2008 12/2008	
See application file for complete search history.			
(56) References Cited			
U.S. PATENT DOCUMENTS			
6,389,463 B2 5/2002 Bolas	2008/0311852 A1	12/2008	Hansen et al.
6,671,494 B1 12/2003 James	2009/0029743 A9	1/2009	Lair et al.
6,674,864 B1 1/2004 Kitamura	2009/0116678 A1	5/2009	Bevirt et al.
6,792,091 B2 9/2004 Lemchen et al.	2009/0129605 A1	5/2009	Camp et al.
6,937,712 B2 8/2005 Lemchen et al.	2009/0248178 A1	10/2009	Paulson et al.
7,003,515 B1 2/2006 Glaser	2010/0290642 A1	11/2010	Haseagawa
7,027,311 B2 4/2006 Vanderelli	2011/0275323 A1	11/2011	Goldman et al.
7,095,455 B2 8/2006 Jordan	2013/0039510 A1	2/2013	Pelland et al.
	2013/0099507 A1	4/2013	Moriya et al.
	2015/0237439 A1	8/2015	Koss et al.
	2017/0318378 A1	11/2017	Koss et al.

US 10,491,982 B1Page 3

(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0249240 A1 8/2018 Koss et al.
2019/0075390 A1 3/2019 Koss et al.
2019/0238970 A1 8/2019 Koss et al.

FOREIGN PATENT DOCUMENTS

WO WO 2006/047724 A2 5/2006
WO WO 2007/136620 A2 11/2007
WO WO 2007/139578 A1 12/2007
WO WO 2008/033478 A1 3/2008
WO WO 2008/054985 A2 5/2008
WO WO 2009/086555 A1 7/2009

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/US09/39754 dated Jun. 11, 2009, 2 pages.

International Preliminary Examination Report for International Application No. PCT/US09/39754 dated Oct. 28, 2010, 8 pages.

Written Opinion of the International Searching Authority for International Application No. PCT/US09/39754 dated Jun. 11, 2009, 5 pages.

IT Review, "LTB 802.11 WiFi Headphones", <http://itreview.belproject.com/item/1536> accessed on Mar. 13, 2008 (4 pages).

* cited by examiner

U.S. Patent

Nov. 26, 2019

Sheet 1 of 16

US 10,491,982 B1




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5





FIG. 6






FIG. 8




FIG. 9

U.S. Patent

Nov. 26, 2019

Sheet 15 of 16

US 10,491,982 B1




FIG. 10




FIG. 11

US 10,491,982 B1

1

SYSTEM WITH WIRELESS EARPHONES**PRIORITY CLAIM**

The present application claims priority as a continuation to U.S. nonprovisional patent application Ser. No. 16/375,879, filed Apr. 5, 2019, which is a continuation of U.S. nonprovisional patent application Ser. No. 16/182,927, filed Nov. 7, 2018, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/962,305, filed Apr. 25, 2018, now U.S. Pat. No. 10,206,025, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/650,362, filed Jul. 14, 2017, now U.S. Pat. No. 9,986,325, issued May 29, 2018, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/293,785, filed Oct. 14, 2016, now U.S. Pat. No. 9,729,959, issued Aug. 8, 2017, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/082,040, filed Mar. 28, 2016, now U.S. Pat. No. 9,497,535, issued Nov. 15, 2016, which is a continuation of U.S. nonprovisional patent application Ser. No. 14/695,696, filed Apr. 24, 2015, now U.S. Pat. No. 9,438,987, issued on Sep. 6, 2016, which is a continuation of U.S. nonprovisional patent application Ser. No. 13/609,409, filed Sep. 11, 2012, now U.S. Pat. No. 9,049,502, issued Jun. 2, 2015, which is a continuation of U.S. nonprovisional patent application Ser. No. 13/459,291, filed Apr. 30, 2012, now U.S. Pat. No. 8,571,544, issued Oct. 29, 2013, which is a continuation of U.S. patent application Ser. No. 12/936,488, filed Dec. 20, 2010, now U.S. Pat. No. 8,190,203, issued May 29, 2012, which is a national stage entry of PCT/US2009/039754, filed Apr. 7, 2009, which claims priority to U.S. provisional patent application Ser. No. 61/123,265, filed Apr. 7, 2008, all of which are incorporated herein by reference in their entireties.

CROSS-REFERENCE TO RELATED APPLICATIONS

U.S. nonprovisional patent application Ser. No. 14/031,938, filed Sep. 13, 2013, now U.S. Pat. No. 8,655,420, issued Feb. 18, 2014, is also a continuation of United States nonprovisional patent application Ser. No. 13/609,409, filed Sep. 11, 2012, now U.S. Pat. No. 9,049,502, mentioned above.

BACKGROUND

Digital audio players, such as MP3 players and iPods, that store and play digital audio files, are very popular. Such devices typically comprise a data storage unit for storing and playing the digital audio, and a headphone set that connects to the data storage unit, usually with a 1/4" or a 3.5 mm jack and associated cord. Often the headphones are in-ear type headphones. The cord, however, between the headphones and the data storage unit can be cumbersome and annoying to users, and the length of the cord limits the physical distance between the data storage unit and the headphones. Accordingly, some cordless headphones have been proposed, such as the Monster iFreePlay cordless headphones from Apple Inc., which include a docking port on one of the earphones that can connect directly to an iPod Shuffle. Because they have the docking port, however, the Monster iFreePlay cordless headphones from Apple are quite large and are not in-ear type phones. Recently, cordless headphones that connect wirelessly via IEEE 802.11 to a WLAN-

2

ready laptop or personal computer (PC) have been proposed, but such headphones are also quite large and not in-ear type phones.

SUMMARY

In one general aspect, the present invention is directed to a wireless earphone that comprises a transceiver circuit for receiving streaming audio from a data source, such as a digital audio player or a computer, over an ad hoc wireless network. When the data source and the earphone are out of range via the ad hoc wireless network, they may transition automatically to a common infrastructure wireless network (e.g., a wireless LAN). If there is no common infrastructure wireless network for both the data source and the earphone, the earphone may connect via an available infrastructure wireless network to a host server. The host server may, for example, broadcast streaming audio to the earphone and/or transmit to the earphone a network address (e.g., an Internet Protocol (IP) address) for a network-connected content server that streams digital audio. The earphone may then connect to the content server using the IP address. The content server may be an Internet radio server, including, for example, an Internet radio server that broadcasts streaming audio from the data source or some other content.

These and other advantageous, unique aspects of the wireless earphone are described below.

FIGURES

Various embodiments of the present invention are described herein by way of example in conjunction with the following figures, wherein:

FIGS. 1A-1E are views of a wireless earphone according to various embodiments of the present invention;

FIGS. 2A-2D illustrate various communication modes for a wireless earphone according to various embodiments of the present invention;

FIG. 3 is a block diagram of a wireless earphone according to various embodiments of the present invention;

FIGS. 4A-4B show the wireless earphone connected to another device according to various embodiments of the present invention;

FIG. 5 is a diagram of a process implemented by a host server according to various embodiments of the present invention;

FIG. 6 is a diagram of a process implemented by the wireless earphone to transition automatically between wireless networks according to various embodiments of the present invention;

FIGS. 7, 8 and 10 illustrate communication systems involving the wireless earphone according to various embodiments of the present invention;

FIG. 9 is a diagram of a headset including a wireless earphone and a microphone according to various embodiments of the present invention; and

FIG. 11 is a diagram of a pair of wireless earphones with a dongle according to various embodiments of the present invention.

DESCRIPTION

In one general aspect, the present invention is directed to a wireless earphone that receives streaming audio data via ad hoc wireless networks and infrastructure wireless networks, and that transitions seamlessly between wireless networks. The earphone may comprise one or more in-ear, on-ear, or

US 10,491,982 B1

3

over-ear speaker elements. Two exemplary in-ear earphone shapes for the wireless earphone **10** are shown in FIGS. **1A** and **1B**, respectively, although in other embodiments the earphone may take different shapes and the exemplary shapes shown in FIGS. **1A** and **1B** are not intended to be limiting. In one embodiment, the earphone transitions automatically and seamlessly, without user intervention, between communication modes. That is, the earphone may transition automatically from an ad hoc wireless network to an infrastructure wireless network, without user intervention. As used herein, an “ad hoc wireless network” is a network where two (or more) wireless-capable devices, such as the earphone and a data source, communicate directly and wirelessly, without using an access point. An “infrastructure wireless network,” on the other hand, is a wireless network that uses one or more access points to allow a wireless-capable device, such as the wireless earphone, to connect to a computer network, such as a LAN or WAN (including the Internet).

FIGS. **1A** and **1B** show example configurations for a wireless earphone **10** according to various embodiments of the present invention. The examples shown in FIGS. **1A** and **1B** are not limiting and other configurations are within the scope of the present invention. As shown in FIGS. **1A** and **1B**, the earphone **10** may comprise a body **12**. The body **12** may comprise an ear canal portion **14** that is inserted in the ear canal of the user of the earphone **10**. In various embodiments, the body **12** also may comprise an exterior portion **15** that is not inserted into user’s ear canal. The exterior portion **15** may comprise a knob **16** or some other user control (such as a dial, a pressure-activated switch, lever, etc.) for adjusting the shape of the ear canal portion **14**. That is, in various embodiments, activation (e.g. rotation) of the knob **16** may cause the ear canal portion **14** to change shape so as to, for example, radially expand to fit snugly against all sides of the user’s ear canal. Further details regarding such a shape-changing earbud earphone are described in application PCT/US08/88656, filed 31 Dec. 2008, entitled “Adjustable Shape Earphone,” which is incorporated herein by reference in its entirety. The earphone **10** also may comprise a transceiver circuit housed within the body **12**. The transceiver circuit, described further below, may transmit and receive the wireless signals, including receive streaming audio for playing by the earphone **10**. The transceiver circuit may be housed in the exterior portion **15** of the earphone **10** and/or in the ear canal portion **14**.

Although the example earphones **10** shown in FIGS. **1A** and **1B** include a knob **16** for adjusting the shape of the ear canal portion **14**, the present invention is not so limited, and in other embodiments, different means besides a knob **16** may be used to adjust the ear canal portion **14**. In addition, in other embodiments, the earphone **10** may not comprise a shape-changing ear canal portion **14**.

In various embodiments, the user may wear two discrete wireless earphones **10**: one in each ear. In such embodiments, each earphone **10** may comprise a transceiver circuit. In such embodiments, the earphones **10** may be connected by a string or some other cord-type connector to keep the earphones **10** from being separated.

In other embodiments, as shown in FIG. **1C**, a headband **19** may connect the two (left and right) earphones **10**. The headband **19** may be an over-the-head band, as shown in the example of FIG. **1C**, or the headband may be a behind-the-head band. In embodiments comprising a headband **19**, each earphone **10** may comprise a transceiver circuit; hence, each earphone **10** may receive and transmit separately the wireless communication signals. In other embodiments compris-

4

ing a headband **19**, only one earphone **10** may comprise the transceiver circuit, and a wire may run along the headband **19** to the other earphone **10** to connect thereby the transceiver circuit to the acoustic transducer in the earphone that does not comprise the transceiver circuit. The embodiment shown in FIG. **1C** comprises on-ear earphones **10**; in other embodiments, in-ear or over-ear earphones may be used.

In other embodiments, the earphone **10** may comprise a hanger bar **17** that allows the earphone **10** to clip to, or hang on, the user’s ear, as shown in the illustrated embodiment of FIGS. **1D-1E**. FIG. **1D** is a perspective view of the earphone and FIG. **1E** is a side view according to one embodiment. As shown in the illustrated embodiment, the earphone **10** may comprise dual speaker elements **106-A**, **106-B**. One of the speaker elements (the smaller one) **106-A** is sized to fit into the cavum concha of the listener’s ear and the other element (the larger one) **106-B** is not. The listener may use the hanger bar to position the earphone on the listener’s ear. In that connection, the hanger bar may comprise a horizontal section that rests upon the upper external curvature of the listener’s ear behind the upper portion of the auricula (or pinna). The earphone may comprise a knurled knob that allows the user to adjust finely the distance between the horizontal section of the hanger bar and the speaker elements, thereby providing, in such embodiments, another measure of adjustability for the user. More details regarding such a dual element, adjustable earphone may be found in U.S. provisional patent application Ser. No. 61/054,238, which is incorporated herein by reference in its entirety.

FIGS. **2A-2D** illustrate various communication modes for a wireless data communication system involving the earphone **10** according to embodiments of the present invention. As shown in FIG. **2A**, the system comprises a data source **20** in communication with the earphone **10** via an ad hoc wireless network **24**. The earphone **10**, via its transceiver circuit (described in more detail below), may communicate wirelessly with a data source **20**, which may comprise a wireless network adapter **22** for transmitting the digital audio wirelessly. For example, the data source **20** may be a digital audio player (DAP), such as an mp3 player or an iPod, or any other suitable digital audio playing device, such as a laptop or personal computer, that stores and/or plays digital audio files. In other embodiments, the data source **20** may generate analog audio, and the wireless network adapter **22** may encode the analog audio into digital format for transmission to the earphone **10**.

The wireless network adapter **22** may be an integral part of the data source **20**, or it may be a separate device that is connected to the data source **20** to provide wireless connectivity for the data source **20**. For example, the wireless network adapter **22** may comprise a wireless network interface card (WNIC) or other suitable transceiver that plugs into a USB port or other port or jack of the data source **20** (such as a TRS connector) to stream data, e.g., digital audio files, via a wireless network (e.g., the ad hoc wireless network **24** or an infrastructure wireless network). The digital audio transmitted from the data source **20** to the earphone **10** via the wireless networks may comprise compressed or uncompressed audio. Any suitable file format may be used for the audio, including mp3, lossy or lossless WMA, Vorbis, Musepack, FLAC, WAV, AIFF, AU, or any other suitable file format.

When in range, the data source **20** may communicate with the earphone **10** via the ad hoc wireless network **24** using any suitable wireless communication protocol, including Wi-Fi (e.g., IEEE 802.11a/b/g/n), WiMAX (IEEE 802.16), Bluetooth, Zigbee, UWB, or any other suitable wireless

US 10,491,982 B1

5

communication protocol. For purposes of the description to follow, it is assumed that the data source **20** and the earphone **10** communicate using a Wi-Fi protocol, although the invention is not so limited and other wireless communication protocols may be used in other embodiments of the invention. The data source **20** and the earphone **10** are considered in range for the ad hoc wireless network **24** when the signal strengths (e.g., the RSSI) of the signals received by the two devices are above a threshold minimum signal strength level. For example, the data source **20** and the earphone **10** are likely to be in range for an ad hoc wireless network when then are in close proximity, such as when the wearer of the earphone **10** has the data source **20** on his/her person, such as in a pocket, strapped to their waist or arm, or holding the data source in their hand.

When the earphone **10** and the data source **20** are out of range for the ad hoc wireless network **24**, that is, when the received signals degrade below the threshold minimum signal strength level, both the earphone **10** and the data source **20** may transition automatically to communicate over an infrastructure wireless network (such as a wireless LAN (WLAN)) **30** that is in the range of both the earphone **10** and the data source **20**, as shown in FIG. 2B. The earphone **10** and the data source **20** (e.g., the wireless network adapter **22**) may include firmware, as described further below, that cause the components to make the transition to a common infrastructure wireless network **30** automatically and seamlessly, e.g., without user intervention. The earphone **10** may cache the received audio in a buffer or memory for a time period before playing the audio. The cached audio may be played after the connection over the ad hoc wireless network is lost to give the earphone **10** and the data source **20** time to connect via the infrastructure wireless network.

For example, as shown in FIG. 2B, the infrastructure network may comprise an access point **32** that is in the range of both the data source **20** and the earphone **10**. The access point **32** may be an electronic hardware device that acts as a wireless access point for, and that is connected to, a wired and/or wireless data communication network **33**, such as a LAN or WAN, for example. The data source **20** and the earphone **10** may both communicate wirelessly with the access point **32** using the appropriate network data protocol (a Wi-Fi protocol, for example). The data source **20** and the earphone **10** may both transition automatically to an agreed-upon WLAN **30** that is in the range of both devices when they cannot communicate satisfactorily via the ad hoc wireless network **24**. A procedure for specifying an agreed-upon infrastructure wireless network **30** is described further below. Alternatively, the infrastructure wireless network **30** may have multiple access points **32a-b**, as shown in FIG. 2C. In such an embodiment, the data source **20** may communicate wirelessly with one access point **32b** and the earphone **10** may communicate wirelessly with another access point **32a** of the same infrastructure wireless network **30**. Again, the data source **20** and the earphone **10** may transition to an agreed-upon WLAN.

If there is no suitable common infrastructure wireless network over which the earphone **10** and the data source **20** can communicate, as shown in FIG. 2D, the earphone **10** may transition to communicate with an access point **32a** for an available (first) wireless network (e.g., WLAN) **30a** that is in the range of the earphone **10**. In this mode, the earphone **10** may connect via the wireless network **30a** to a network-enabled host server **40**. The host server **40** may be connected to the wireless network **30a** via an electronic data communication network **42**, such as the Internet. In one mode, the host server **40** may transmit streaming digital audio via the

6

networks **33a**, **42** to the earphone **10**. In another mode, the host server **40** may transmit to the earphone **10** a network address, such as an Internet Protocol (IP) address, for a streaming digital audio content server **70** on the network **42**. Using the received IP address, the earphone **10** may connect to the streaming digital audio content server **70** via the networks **30a**, **42** to receive and process digital audio from the streaming digital audio content server **70**.

The digital audio content server **70** may be, for example, an Internet radio station server. The digital audio content server **70** may stream digital audio over the network **42** (e.g., the Internet), which the earphone **10** may receive and process. In one embodiment, the streaming digital audio content server **70** may stream digital audio received by the streaming digital audio content server **70** from the data source **20**. For example, where the data source **20** is a wireless-capable device, such as a portable DAP, the data source **20** may connect to the streaming digital audio content server **70** via a wireless network **30b** and the network **42**. Alternatively, where for example the data source **20** is non-wireless-capable device, such as a PC, the data source **20** may have a direct wired connection to the network **42**. After being authenticated by the streaming digital audio content server **70**, the data source **20** may stream digital audio to the streaming digital audio content server **70**, which may broadcast the received digital audio over the network **42** (e.g., the Internet). In such a manner, the user of the earphone **10** may listen to audio from the data source **20** even when (i) the earphone **10** and the data source **20** are not in communication via an ad hoc wireless network **24** and (ii) the earphone **10** and the data source **20** are not in communication via a common local infrastructure wireless network **30**.

FIG. 3 is a block diagram of the earphone **10** according to various embodiments of the present invention. In the illustrated embodiment, the earphone **10** comprises a transceiver circuit **100** and related peripheral components. As shown in FIG. 3, the peripheral components of the earphone **10** may comprise a power source **102**, a microphone **104**, one or more acoustic transducers **106** (e.g., speakers), and an antenna **108**. The transceiver circuit **100** and some of the peripheral components (such as the power source **102** and the acoustic transducers **106**) may be housed within the body **12** of the earphone **10** (see FIG. 1). Other peripheral components, such as the microphone **104** and the antenna **108** may be external to the body **12** of the earphone **10**. In addition, some of the peripheral components, such as the microphone **104**, are optional in various embodiments.

In various embodiments, the transceiver circuit **100** may be implemented as a single integrated circuit (IC), such as a system-on-chip (SoC), which is conducive to miniaturizing the components of the earphone **10**, which is advantageous if the earphone **10** is to be relatively small in size, such as an in-ear earphone (see FIGS. 1A-1B for example). In alternative embodiments, however, the components of the transceiver circuit **100** could be realized with two or more discrete ICs or other components, such as separate ICs for the processors, memory, and RF (e.g., Wi-Fi) module, for example.

The power source **102** may comprise, for example, a rechargeable or non-rechargeable battery (or batteries). In other embodiments, the power source **102** may comprise one or more ultracapacitors (sometimes referred to as supercapacitors) that are charged by a primary power source. In embodiments where the power source **102** comprises a rechargeable battery cell or an ultracapacitor, the battery cell or ultracapacitor, as the case may be, may be charged for use,

US 10,491,982 B1

7

for example, when the earphone 10 is connected to a docking station or computer. The docking station may be connected to or part of a computer device, such as a laptop computer or PC. In addition to charging the rechargeable power source 102, the docking station and/or computer may facilitate downloading of data to and/or from the earphone 10. In other embodiments, the power source 102 may comprise capacitors passively charged with RF radiation, such as described in U.S. Pat. No. 7,027,311. The power source 102 may be coupled to a power source control module 103 of transceiver circuit 100 that controls and monitors the power source 102.

The acoustic transducer(s) 106 may be the speaker element(s) for conveying the sound to the user of the earphone 10. According to various embodiments, the earphone 10 may comprise one or more acoustic transducers 106. For embodiments having more than one transducer, one transducer may be larger than the other transducer, and a crossover circuit (not shown) may transmit the higher frequencies to the smaller transducer and may transmit the lower frequencies to the larger transducer. More details regarding dual element earphones are provided in U.S. Pat. No. 5,333,206, assigned to Koss Corporation, which is incorporated herein by reference in its entirety.

The antenna 108 may receive and transmit the wireless signals from and to the wireless networks 24, 30. A RF (e.g., Wi-Fi) module 110 of the transceiver circuit 100 in communication with the antenna 108 may, among other things, modulate and demodulate the signals transmitted from and received by the antenna 108. The RF module 110 communicates with a baseband processor 112, which performs other functions necessary for the earphone 10 to communicate using the Wi-Fi (or other communication) protocol.

The baseband processor 112 may be in communication with a processor unit 114, which may comprise a microprocessor 116 and a digital signal processor (DSP) 118. The microprocessor 116 may control the various components of the transceiver circuit 100. The DSP 114 may, for example, perform various sound quality enhancements to the digital audio received by the baseband processor 112, including noise cancellation and sound equalization. The processor unit 114 may be in communication with a volatile memory unit 120 and a non-volatile memory unit 122. A memory management unit 124 may control the processor unit's access to the memory units 120, 122. The volatile memory 122 may comprise, for example, a random access memory (RAM) circuit. The non-volatile memory unit 122 may comprise a read only memory (ROM) and/or flash memory circuits. The memory units 120, 122 may store firmware that is executed by the processor unit 114. Execution of the firmware by the processor unit 114 may provide various functionality for the earphone 10, such as the automatic transition between wireless networks as described herein. The memory units 120, 122 may also cache received digital audio.

A digital-to-analog converter (DAC) 125 may convert the digital audio from the processor unit 114 to analog form for coupling to the acoustic transducer(s) 106. An I²S interface 126 or other suitable serial or parallel bus interface may provide the interface between the processor unit 114 and the DAC 125. An analog-to-digital converter (ADC) 128, which also communicates with the I²S interface 126, may convert analog audio signals picked up by the microphone 104 for processing by the processor unit 114.

The transceiver circuit 100 also may comprise a USB or other suitable interface 130 that allows the earphone 10 to be connected to an external device via a USB cable or other

8

suitable link. As shown in FIG. 4A, the external device may be a docking station 200 connected to a computer device 202. Also, in various embodiments, the earphone 10 could be connected directly to the computer 202 without the docking station 200. In addition, the external device may be a DAP 210, as shown in FIG. 4B. In that way, the earphone 10 could connect directly to a data source 20, such as the DAP 210 or the computer 202, through the USB port 130. In addition, through the USB port 130, the earphone 10 may connect to a PC 202 or docking station 202 to charge up the power source 102 and/or to get downloads (e.g., data or firmware).

According to various embodiments, the earphone 10 may have an associated web page that a user may access through the host server 40 (see FIG. 2D) or some other server. An authenticated user could log onto the website from a client computing device 50 (e.g., laptop, PC, handheld computer device, etc., including the data source 20) (see FIG. 2D) to access the web page for the earphone 10 to set various profile values for the earphone 10. For example, at the web site, the user could set various content features and filters, as well as adjust various sound control features, such as treble, bass, frequency settings, noise cancellation settings, etc. In addition, the user could set preferred streaming audio stations, such as preferred Internet radio stations or other streaming audio broadcasts. That way, instead of listening to streaming audio from the data source 20, the user could listen to Internet radio stations or other streaming audio broadcasts received by the earphone 10. In such an operating mode, the earphone user, via the web site, may prioritize a number of Internet radio stations or other broadcast sources (hosted by streaming digital audio content servers 70). With reference to FIG. 7, the host server 40 may send the IP address for the earphone user's desired (e.g., highest priority) Internet radio station to the earphone 10. A button 11 on the earphone 10, such as on the rotating dial 16 as shown in the examples of FIGS. 1A and 1B, may allow the user to cycle through the preset preferred Internet radio stations. That is, for example, when the user presses the button 11, an electronic communication may be transmitted to the host server 40 via the wireless network 30, and in response to receiving the communication, the host server 40 may send the IP address for the user's next highest rated Internet radio station via the network 42 to the earphone 10. The earphone 10 may then connect to the streaming digital audio content server 70 for that Internet radio station using the IP address provided by the host server 40. This process may be repeated, e.g., cycled through, for each preset Internet radio station configured by the user of the earphone 10.

At the web site for the earphone 10 hosted on the host server 40, in addition to establishing the identification of digital audio sources (e.g., IDs for the user's DAP or PC) and earphones, the user could set parental or other user controls. For example, the user could restrict certain Internet radio broadcasts based on content or parental ratings, etc. That is, for example, the user could configure a setting through the web site that prevents the host server 40 from sending an IP address for a streaming digital audio content server 70 that broadcasts explicit content based on a rating for the content. In addition, if a number of different earphones 10 are registered to the same user, the user could define separate controls for the different earphones 10 (as well as customize any other preferences or settings particular to the earphones 10, including Internet radio stations, sound quality settings, etc. that would later be downloaded to the earphones 10). In addition, in modes where the host server 40 streams audio to the earphone 10, the host server

9

40 may log the files or content streamed to the various earphones 10, and the user could view at the web site the files or content that were played by the earphones 10. In that way, the user could monitor the files played by the earphones 10.

In addition, the host server 40 may provide a so-called eavesdropping function according to various embodiments. The eavesdropping service could be activated via the web site. When the service is activated, the host server 40 may transmit the content that it is delivering to a first earphone 10a to another, second earphone 10b, as shown in FIG. 8. Alternatively, the host server 40 may transmit to the second earphone 10b the most recent IP address for a streaming digital audio content server 70 that was sent to the first earphone 10a. The second earphone 10b may then connect to the streaming digital audio content server 70 that the first earphone 10a is currently connected. That way, the user of the second earphone 10b, which may be a parent, for example, may directly monitor the content being received by the first earphone 10a, which may belong to a child of the parent.

This function also could be present in the earphones 10 themselves, allowing a parent (or other user) to join an ad-hoc wireless network and listen to what their child (or other listener) is hearing. For example, with reference to FIG. 10, a first earphone 10a may receive wireless audio, such as from the data source 20 or some other source, such as the host server 40. The first earphone 10a may be programmed with firmware to broadcast the received audio to a second earphone 10b via an ad hoc wireless network 24. That way, the wearer of the second earphone 10b can monitor in real-time the content being played by the first earphone 10a.

At the web site, the user may also specify the identification number ("ID") of their earphone(s) 10, and the host server 40 may translate the ID to the current internet protocol (IP) addresses for the earphone 10 and for the data source 20. This allows the user to find his or her data source 20 even when it is behind a firewall or on a changing IP address. That way, the host server 40 can match the audio from the data source 20 to the appropriate earphone 10 based on the specified device ID. The user also could specify a number of different data sources 20. For example, the user's DAP may have one specified IP address and the user's home (or work) computer may have another specified IP address. Via the web site hosted by the host server 40, the user could specify or prioritize from which source (e.g., the user's DAP or computer) the earphone 10 is to receive content.

The host server 40 (or some other server) may also push firmware upgrades and/or data updates to the earphone 10 using the IP addresses of the earphone 10 via the networks 30, 42. In addition, a user could download the firmware upgrades and/or data updates from the host server 40 to the client computing device 202 (see FIG. 4A) via the Internet, and then download the firmware upgrades and/or data updates to the earphone 10 when the earphone 10 is connected to the client computer device 202 (such as through a USB port and/or the docking station 200).

Whether the downloads are transmitted wirelessly to the earphone 10 or via the client computing device 202 may depend on the current data rate of the earphone 10 and the quantity of data to be transmitted to the earphone 10. For example, according to various embodiments, as shown in the process flow of FIG. 5, the host server 40 may be programmed, at step 50, to make a determination, based on the current data rate for the earphone 10 and the size of the update, whether the update should be pushed to the earphone

10

10 wirelessly (e.g., via the WLAN 30a in FIG. 2D). If the update is too large and/or the current data rate is too low that the performance of the earphone 10 will be adversely affected, the host server 40 may refrain from pushing the update to the earphone 10 wirelessly and wait instead to download the update to the client computing device 202 at step 51. Conversely, if the host server 40 determines that, given the size of the update and the current data rate for the earphone 10 that the performance of the earphone 10 will not be adversely affected, the host server 40 may transmit the update wirelessly to the earphone 10 at step 52.

As mentioned above, the processor unit 114 of the speakerphones 14 may be programmed, via firmware stored in the memory 120, 122, to have the ability to transition automatically from the ad hoc wireless network 24 to an infrastructure wireless network 30 (such as a WLAN) when the quality of the signal on the ad hoc wireless network 24 degrades below a suitable threshold (such as when the data source 20 is out of range for an ad hoc wireless network). In that case, the earphone 10 and the data source 20 may connect to a common infrastructure wireless network (e.g., WLAN) (see, for example, FIGS. 2B-2C). Through the web site for the earphone 10, described above, the user could specify a priority of infrastructure wireless networks 30 for the data source 20 and the earphone 10 to connect to when the ad hoc wireless network 24 is not available. For example, the user could specify a WLAN servicing his/her residence first, a WLAN servicing his/her place of employment second, etc. During the time that the earphone 10 and the data source 20 are connected via the ad hoc wireless network 24, the earphone 10 and the data source 20 may exchange data regarding which infrastructure networks are in range. When the earphone 10 and the data source 20 are no longer in range for the ad hoc wireless network 24 (that is, for example, the signals between the device degrade below an acceptable level), they may both transition automatically to the highest prioritized infrastructure wireless network whose signal strength is above a certain threshold level. That way, even though the earphone 10 and the data source 20 are out of range for the ad hoc wireless network 24, the earphone 10 may still receive the streaming audio from the data source 20 via the infrastructure wireless network 30 (see FIGS. 2B-2C).

When none of the preferred infrastructure networks is in range, the earphone 10 may connect automatically to the host server 40 via an available infrastructure wireless network 30 (see FIG. 2D), e.g., the infrastructure wireless network 30 having the highest RSSI and to which the earphone 10 is authenticated to use. The host server 40, as mentioned above, may transmit IP addresses to the earphone 10 for streaming digital audio content servers 70 or the host sever 40 may stream digital audio to the earphone 10 itself when in this communication mode.

FIG. 6 is a diagram of the process flow, according to one embodiment, implemented by the transceiver circuit 100 of the earphone 10. The process shown in FIG. 6 may be implemented in part by the processor unit 114 executing firmware stored in a memory unit 120, 122 of the transceiver circuit 100. At step 61, the earphone 10 may determine if it can communicate with the data source 20 via an ad hoc wireless network 24. That is, the earphone 10 may determine if the strength of the wireless signals from the data source 20 exceed some minimum threshold. If so, the data source 20 and the earphone 10 may communicate wirelessly via the ad hoc wireless network 24 (see FIG. 2A). While in this communication mode, at step 62, the data source 20 and the earphone 10 also may exchange data regarding the local

US 10,491,982 B1

11

infrastructure wireless networks, if any, in the range of the data source 20 and the earphone 10, respectively. For example, the earphone 10 may transmit the ID of local infrastructure wireless networks 30 that the earphone 10 can detect whose signal strength (e.g., RSSI) exceeds some minimum threshold level. Similarly, the data source 20 may transmit the ID the local infrastructure wireless networks 30 that the data source 20 can detect whose signal strength (e.g., RSSI) exceeds some minimum threshold level. The earphone 10 may save this data in a memory unit 120, 122. Similarly, the data source 20 may store in memory the wireless networks that the earphone 10 is detected.

The data source 20 and the earphone 10 may continue to communicate via the ad hoc wireless network mode 24 until they are out of range (e.g., the signal strengths degrade below a minimum threshold level). If an ad hoc wireless network 24 is not available at block 61, the transceiver circuit 100 and the data source 20 may execute a process, shown at block 63, to connect to the user's highest prioritized infrastructure wireless network 30. For example, of the infrastructure wireless networks whose signal strength exceeded the minimum threshold for both the earphone 10 and the data source 20 determined at step 62, the earphone 10 and the data source 20 may both transition to the infrastructure wireless network 30 having the highest priority, as previously set by the user (seen FIGS. 2B-2C, for example). For example, if the user's highest prioritized infrastructure wireless network 30 is not available, but the user's second highest prioritized infrastructure wireless network 30 is, the earphone 10 and the data source 20 may both transition automatically to the user's second highest prioritized infrastructure wireless network 30 at block 64. As shown by the loop with block 65, the earphone 10 and the data source 20 may continue to communicate via one of the user's prioritized infrastructure wireless networks 30 as long as the infrastructure wireless network 30 is available. If the infrastructure wireless network becomes unavailable, the process may return to block 61.

If, however, no ad hoc wireless network and none of the user's prioritized infrastructure wireless networks are available, the earphone 10 may transition automatically to connect to the host server 40 at block 66 (see FIG. 2D) using an available infrastructure wireless network 30. At block 67, the host server 40 may transmit an IP address to the earphone 10 for one of the streaming digital audio content servers 70, and at block 68 the earphone 10 may connect to the streaming digital audio content server 70 using the received IP address. At step 69, as long as the earphone 10 is connected to the streaming digital audio content server 70, the earphone 10 may continue to communicate in this mode. However, if the earphone 10 loses its connection to the digital audio content server 70, the process may return to block 61 in one embodiment. As mentioned above, at block 67, instead of sending an IP address for a streaming digital audio content server 70, the host server 40 may stream digital audio to the earphone 10. The user, when configuring their earphone 10 preferences via the web site, may specify and/or prioritize whether the host server 40 is to send IP addresses for the streaming digital audio content servers 70 and/or whether the host server 40 is to stream audio to the earphone 10 itself.

In another embodiment, the earphone 10 may be programmed to transition automatically to the host server 40 when the earphone 10 and the data source 20 are not in communication via the ad hoc wireless network 24. That is, in such an embodiment, the earphone 10 may not try to connect via a local infrastructure wireless network 30 with

12

the data source 20, but instead transition automatically to connect to the host server 40 (see FIG. 2D).

In various embodiments, as shown in FIG. 1B, the button 11 or other user selection device that allows the wearer of the earphone 10 to indicate approval and/or disapproval of songs or other audio files listened to by the wearer over an Internet radio station. The approval/disapproval rating, along with metadata for the song received by the earphone 10 with the streaming audio, may be transmitted from the transceiver circuit 100 of the earphone 10 back to the host server 40, which may log the songs played as well as the ratings for the various songs/audio files. In addition to being able to view the logs at the website, the host server 40 (or some other server) may send an email or other electronic communication to the earphone user, at a user specified email address or other address, which the user might access from their client communication device 50 (see FIG. 2D). The email or other electronic communication may contain a listing of the song/audio files for which the user gave approval ratings using the button 11 or other user selection device. Further, the email or other electronic communication may provide a URL link for a URL at which the user could download song/audio files that the user rated (presumably song/audio files for which the user gave an approval rating). In some instances, the user may be required to pay a fee to download the song/audio file.

The user song ratings also may be used by the host server 40 to determine the user's musical preferences and offer new music that the user might enjoy. More details about generating user play lists based on song ratings may be found in published U.S. patent applications Pub. No. 2006/0212444, Pub. No. 2006/0206487, and Pub. No. 2006/0212442, and U.S. Pat. No. 7,003,515, which are incorporated herein by reference in their entirety.

In addition or alternatively, the user could log onto a web site hosted by the host server 40 (or some other server) to view the approval/disapproval ratings that the user made via the button 11 on the earphone 10. The web site may provide the user with the option of downloading the rated songs/audio files (for the host server 40 or some other server system) to their client computer device 50. The user could then have their earphone 10 connect to their client computer device 50 as a data source 20 via an ad hoc wireless network 24 (see FIG. 2A) or via an infrastructure wireless network (see FIGS. 2B-2D) to listen to the downloaded songs. In addition, the user could download the song files from their client computer device 50 to their DAP and listen to the downloaded song files from their DAP by using their DAP as the data source 20 in a similar manner.

Another application of the headsets may be in vehicles equipped with Wi-Fi or other wireless network connectivity. Published PCT application WO 2007/136620, which is incorporated herein by reference, discloses a wireless router for providing a Wi-Fi or other local wireless network for a vehicle, such as a car, truck, boat, bus, etc. In a vehicle having a Wi-Fi or other local wireless network, the audio for other media systems in the vehicle could be broadcast over the vehicle's wireless network. For example, if the vehicle comprises a DVD player, the audio from the DVD system could be transmitted to the router and broadcast over the vehicle's network. Similarly, the audio from terrestrial radio stations, a CD player, or an audio cassette player could be broadcast over the vehicle's local wireless network. The vehicle's passengers, equipped with the earphones 10, could cycle through the various audio broadcasts (including the broadcasts from the vehicle's media system as well as broadcasts from the host server 40, for example) using a

US 10,491,982 B1

13

selection button 11 on the earphone 10. The vehicle may also be equipped with a console or terminal, etc., through which a passenger could mute all of the broadcasts for direct voice communications, for example.

As described above, the earphones 10 may also include a microphone 104, as shown in the example of FIG. 9. The headset 90 shown in FIG. 9 includes two earphones 10, both of which may include a transceiver circuit 100 or only one of which may include the transceiver circuit, as discussed above. The microphone 104 could be used to broadcast communications from one earphone wearer to another earphone wearer. For example, one wearer could activate the microphone by pressing a button 92 on the headset 90. The headset 90 may then transmit a communication via an ad hoc wireless network 24 or other wireless network to a nearby recipient (or recipients) equipped with a headset 90 with a transceiver circuit 100 in one or both of the earphones 10. When such communication is detected by the recipient's headset 90, the streaming audio received over the wireless network by the recipient's headset 90 may be muted, and the intercom channel may be routed to the transducer(s) of the recipient's headset 90 for playing for the recipient. This functionality may be valuable and useful where multiple wearers of the headsets 90 are in close proximity, such as on motorcycles, for example.

Another exemplary use of the earphones 10 is in a factory, warehouse, construction site, or other environment that might be noisy. Persons (e.g., workers) in the environment could use the earphones 10 for protection from the surrounding noise of the environment. From a console or terminal, a person (e.g., a supervisor) could select a particular recipient for a communication over the Wi-Fi network (or other local wireless network). The console or terminal may have buttons, dials, or switches, etc., for each user/recipient, or it could have one button or dial through which the sender could cycle through the possible recipients. In addition, the console or terminal could have a graphical user interface, through which the sender may select the desired recipient(s).

As mentioned above, the earphones 10 may comprise a USB port. In one embodiment, as shown in FIG. 11, the user may use an adapter 150 that connects to the USB port of each earphone 10. The adapter 150 may also have a plug connector 152, such as a 3.5 mm jack, which allows the user to connect the adapter 150 to devices having a corresponding port for the connector 152. When the earphones 10 detect a connection via their USB interfaces in such a manner, the Wi-Fi (or other wireless protocol) components may shut down or go into sleep mode, and the earphones 10 will route standard headphone level analog signals to the transducer(s) 106. This may be convenient in environments where wireless communications are not permitted, such as airplanes, but where there is a convenient source of audio contact. For example, the adapter 150 could plug into a person's DAP. The DSP 118 of the earphone 10 may still be operational in such a non-wireless mode to provide noise cancellation and any applicable equalization.

The examples presented herein are intended to illustrate potential and specific implementations of the embodiments. It can be appreciated that the examples are intended primarily for purposes of illustration for those skilled in the art. No particular aspect of the examples is/are intended to limit the scope of the described embodiments.

According to various embodiments, therefore, the present invention is directed to an earphone 10 that comprises a body 12, where the body 12 comprises: (i) at least one acoustic transducer 106 for converting an electrical signal to sound; (ii) an antenna 108; and (iii) a transceiver circuit 100

14

in communication with the at least one acoustic transducer 106 and the antenna 108. The transceiver circuit 100 is for receiving and transmitting wireless signals via the antenna 108, and the transceiver circuit 100 is for outputting the electrical signal to the at least one acoustic transducer 106. The wireless transceiver circuit also comprises firmware, which when executed by the transceiver circuit, causes the transceiver circuit to: (i) receive digital audio wirelessly from a data source 20 via an ad hoc wireless network 24 when the data source 20 is in wireless communication range with the earphone 10 via the ad hoc wireless network 24; and (ii) when the data source 20 is not in wireless communication range with the earphone 10 via the ad hoc wireless network 24, transition automatically to receive digital audio via an infrastructure wireless network 30.

According to various implementations, the data source may comprise a portable digital audio player, such as an MP3 player, iPod, or laptop computer, or a nonportable digital audio player, such as a personal computer. In addition, the transceiver circuit 100 may comprise: (i) a wireless communication module 110 (such as a Wi-Fi or other wireless communication protocol module); (ii) a processor unit 114 in communication with the wireless communication module 110; (iii) a non-volatile memory unit 122 in communication with the processor unit 114; and (iv) a volatile memory 120 unit in communication with the processor unit 114. The infrastructure wireless network may comprise a WLAN. The transceiver circuit 100 may receive digital audio from the data source 20 via the infrastructure wireless network 30 when the data source 20 is not in wireless communication range with the earphone 10 via the ad hoc wireless network 24. The transceiver circuit firmware, when executed by the transceiver circuit 100, may cause the transceiver circuit 100 of the earphone 10 to transition automatically to a pre-set infrastructure wireless network 30 that the data source 20 transitions to when the data source 20 is not in wireless communication range with the earphone 10 via the ad hoc wireless network 24 and when the pre-set infrastructure wireless network 30 is in range of both the earphone 10 and the data source 20. In addition, the transceiver circuit firmware, when executed by the transceiver circuit 100, may cause the transceiver circuit 100 of the earphone 10 to transmit data via the ad hoc wireless network 24 to the data source 20 regarding one or more infrastructure wireless networks 30 detected by the transceiver circuit 100 when the earphone 10 and the data source 20 are communicating via the ad hoc wireless network 24.

In addition, the transceiver circuit firmware, when executed by the transceiver circuit 100, may cause the transceiver circuit 100 of the earphone 10 to connect to a host server 40 via an available infrastructure wireless network 30 when the data source 20 is not in wireless communication range with the earphone 10 via the ad hoc wireless network 24. The earphone 10 may receive streaming digital audio from the host server 40 via the infrastructure wireless network 30. In addition, the earphone 10 may receive a first network address for a first streaming digital audio content server 70 from the host server 40 via the infrastructure wireless network 30. In addition, the earphone 10 may comprise a user control, such as button 11, dial, pressure switch, or other type of user control, that, when activated, causes the earphone 10 to transmit an electronic request via the infrastructure wireless network 30 to the host server 40 for a second network address for a second streaming digital audio content server 70.

In other embodiments, the present invention is directed to a system that comprises: (i) a data source 20 for wirelessly

US 10,491,982 B1

15

transmitting streaming digital audio; and (ii) a wireless earphone 10 that is in wireless communication with the data source 20. In yet other embodiments, the present invention is directed to a communication system that comprises: (i) a host server 40; (ii) a first streaming digital audio content server 70 that is connected to the host server 40 via a data network 42; and (iii) a wireless earphone 10 that is in communication with the host server 40 via a wireless network 30. The host server 40 is programmed to transmit to the earphone 10 a first network address for the first streaming digital audio content server 70 on the data network 42. The host server 40 and the streaming digital audio content server(s) 70 each may comprise one or more processor circuits and one or more memory circuits (e.g., ROM circuits and/or RAM circuits).

In yet another embodiment, the present invention is directed to a headset that comprises: (i) a first earphone 10a that comprises one or more acoustic transducers 10b for converting a first electrical signal to sound; and (ii) a second earphone 10b, connected to the first earphone 10a, wherein the second earphone 10b comprises one or more acoustic transducers 10b for converting a second electrical signal to sound. In one embodiment, the first earphone 10a comprises: (i) a first antenna 108; and (ii) a first transceiver circuit 100 in communication with the one or more acoustic transducers 106 of the first earphone 10a and in communication with the first antenna 108. The first transceiver circuit 100 is for receiving and transmitting wireless signals via the first antenna 108, and for outputting the first electrical signal to the one or more acoustic transducers 10b of the first earphone 10a. The first transceiver circuit 100 also may comprise firmware, which when executed by the first transceiver circuit 100, causes the first transceiver circuit 100 to: (i) receive digital audio wirelessly from a data source 20 via an ad hoc wireless network 24 when the data source 20 is in wireless communication range with the first earphone 10a via the ad hoc wireless network 24; and (ii) when the data source 20 is not in wireless communication range with the first earphone 10a via the ad hoc wireless network 24, transition automatically to receive digital audio via an infrastructure wireless network 30.

In various implementations, the headset further may comprise a head band 19 that is connected to the first and second earphones 10. In addition, the headset 19 further may comprise a microphone 104 having an output connected to the first transceiver circuit 100. In one embodiment, the first transceiver circuit 100 is for outputting the second electrical signal to the one or more acoustic transducers 106 of the second earphone 10b. In another embodiment, the second earphone 10b comprises: (i) a second antenna 108; and (ii) a second transceiver circuit 100 in communication with the one or more acoustic transducers 106 of the second earphone 10b and in communication with the second antenna 108. The second transceiver circuit 100 is for receiving and transmitting wireless signals via the second antenna 108, and for outputting the second electrical signal to the one or more acoustic transducers 106 of the second earphone 10b. The second transceiver circuit 100 may comprise firmware, which when executed by the second transceiver circuit 100, causes the second transceiver circuit 100 to: (i) receive digital audio wirelessly from the data source 20 via the ad hoc wireless network 24 when the data source 20 is in wireless communication range with the second earphone 10b via the ad hoc wireless network 24; and (ii) when the data source 20 is not in wireless communication range with the second earphone 10b via the ad hoc wireless network 24,

16

transition automatically to receive digital audio via the infrastructure wireless network 30.

In addition, according to various embodiments, the first earphone 10a may comprise a first data port and the second earphone 10b may comprise a second data port. In addition, the headset may further comprise an adapter or dongle 150 connected to the first data port of the first earphone 10a and to the second data port of the second earphone 10b, wherein the adapter 150 comprises an output plug connector 152 for connecting to a remote device.

In addition, according to other embodiments, the present invention is directed to a method that comprises the steps of: (i) receiving, by a wireless earphone, via an ad hoc wireless network, digital audio from a data source when the data source is in wireless communication with the earphone via the ad hoc wireless network; (ii) converting, by the wireless earphone, the digital audio to sound; and (iii) when the data source is not in wireless communication with the earphone, transitioning automatically, by the earphone, to receive digital audio via an infrastructure wireless network.

In various implementations, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network may comprise transitioning automatically to receive digital audio from the data source via an infrastructure wireless network when the data source is not in wireless communication range with the earphone via the ad hoc wireless network. In addition, the method may further comprise the step of receiving by the wireless earphone from the data source via the ad hoc wireless network data regarding one or more infrastructure wireless networks detected by data source when the earphone and the data source are communicating via the ad hoc wireless network.

In addition, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network comprises may transitioning automatically to receive digital audio from a host sever via the infrastructure wireless network when the data source is not in wireless communication range with the earphone via the ad hoc wireless network. Additionally, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network may comprise: (i) receiving, by the wireless earphone via the infrastructure wireless network, from a host server connected to the infrastructure wireless network, a network address for a streaming digital audio content server; and (ii) connecting, by the wireless earphone, to the streaming digital audio content server using the network address received from the host server.

It is to be understood that the figures and descriptions of the embodiments have been simplified to illustrate elements that are relevant for a clear understanding of the embodiments, while eliminating, for purposes of clarity, other elements. For example, certain operating system details for the various computer-related devices and systems are not described herein. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable in a typical processor or computer system. Because such elements are well known in the art and because they do not facilitate a better understanding of the embodiments, a discussion of such elements is not provided herein.

In general, it will be apparent to one of ordinary skill in the art that at least some of the embodiments described herein may be implemented in many different embodiments of software, firmware and/or hardware. The software and firmware code may be executed by a processor or any other similar computing device. The software code or specialized control hardware that may be used to implement embodi-

US 10,491,982 B1

17

ments is not limiting. For example, embodiments described herein may be implemented in computer software using any suitable computer software language type. Such software may be stored on any type of suitable computer-readable medium or media, such as, for example, a magnetic or optical storage medium. The operation and behavior of the embodiments may be described without specific reference to specific software code or specialized hardware components. The absence of such specific references is feasible, because it is clearly understood that artisans of ordinary skill would be able to design software and control hardware to implement the embodiments based on the present description with no more than reasonable effort and without undue experimentation.

Moreover, the processes associated with the present embodiments may be executed by programmable equipment, such as computers or computer systems and/or processors. Software that may cause programmable equipment to execute processes may be stored in any storage device, such as, for example, a computer system (nonvolatile) memory, an optical disk, magnetic tape, or magnetic disk. Furthermore, at least some of the processes may be programmed when the computer system is manufactured or stored on various types of computer-readable media.

A “computer,” “computer system,” “host,” “host server,” “server,” or “processor” may be, for example and without limitation, a processor, microcomputer, minicomputer, server, mainframe, laptop, personal data assistant (PDA), wireless e-mail device, cellular phone, pager, processor, fax machine, scanner, or any other programmable device configured to transmit and/or receive data over a network. Such components may comprise: one or more processor circuits; and one more memory circuits, including ROM circuits and RAM circuits. Computer systems and computer-based devices disclosed herein may include memory for storing certain software applications used in obtaining, processing, and communicating information. It can be appreciated that such memory may be internal or external with respect to operation of the disclosed embodiments. The memory may also include any means for storing software, including a hard disk, an optical disk, floppy disk, ROM (read only memory), RAM (random access memory), PROM (programmable ROM), EEPROM (electrically erasable PROM) and/or other computer-readable media.

In various embodiments disclosed herein, a single component may be replaced by multiple components and multiple components may be replaced by a single component to perform a given function or functions. Except where such substitution would not be operative, such substitution is within the intended scope of the embodiments. Any servers described herein, such as the host server 40, for example, may be replaced by a “server farm” or other grouping of networked servers (such as server blades) that are located and configured for cooperative functions. It can be appreciated that a server farm may serve to distribute workload between/among individual components of the farm and may expedite computing processes by harnessing the collective and cooperative power of multiple servers. Such server farms may employ load-balancing software that accomplishes tasks such as, for example, tracking demand for processing power from different machines, prioritizing and scheduling tasks based on network demand and/or providing backup contingency in the event of component failure or reduction in operability.

While various embodiments have been described herein, it should be apparent that various modifications, alterations, and adaptations to those embodiments may occur to persons

18

skilled in the art with attainment of at least some of the advantages. The disclosed embodiments are therefore intended to include all such modifications, alterations, and adaptations without departing from the scope of the embodiments as set forth herein.

What is claimed is:

1. A system comprising:

headphones comprising a pair of first and second wireless earphones to be worn simultaneously by a user, wherein the first and second earphones are separate such that when the headphones are worn by the user, the first and second earphones are not physically connected, wherein each of the first and second earphones comprises:

a body portion that comprises:

a wireless communication circuit for receiving and transmitting wireless signals;

a processor circuit in communication with the wireless communication circuit; and

an ear canal portion that is inserted into an ear of the user when worn by the user; and

at least one acoustic transducer connected to the processor circuit; and

an elongated portion that extends away from the body portion such that the elongated portion extends downwardly when the ear canal portion is inserted in the ear of the user;

a microphone connected to the processor circuit and for picking up utterances of a user of the headphones;

an antenna connected to the wireless communication circuit; and

a rechargeable power source; and

a mobile, digital audio player that stores digital audio content and that comprises a wireless transceiver for transmitting digital audio content to the headphones via Bluetooth wireless communication links, such that each earphone receives and plays audio content received wirelessly via the Bluetooth wireless communication links from the mobile, digital audio player.

2. The system of claim 1, further comprising a docking station for holding at least the first wireless earphone, wherein the docking station comprises a power cable for connecting to an external device for charging the at least the first wireless earphone when the docking station is connected to the external device via the power cable.

3. The system of claim 1, wherein:

in a first operational mode, the pair of first and second earphones play audio content stored on the mobile, digital audio player and transmitted to the first and second earphones from the mobile, digital audio player via the Bluetooth wireless communication links; and

in a second operational mode, the pair of first and second earphones play audio content streamed from a remote network server.

4. The system of claim 1, wherein the processor circuit of the first earphone is for, upon activation of a user control of the headphones, initiating transmission of a request to a remote network server that is remote from the mobile, digital audio player and in communication with the mobile, digital audio player via a data communication network.

5. The system of claim 4, wherein the processor circuit of the first earphone is further for receiving a response to the request.

6. The headphones of claim 5, wherein:

the mobile digital audio player is a first digital audio source;

US 10,491,982 B1

19

the system further comprises a second digital audio player that is different from the first digital audio player; and the headphones transition to play digital audio content received wirelessly from the second digital audio source via a second wireless communication link based on, at least in part, a signal strength for the second wireless communication link.

7. The headphones of claim 6, wherein the processor circuits of the headphones are configured to receive firmware upgrades pushed from a remote network server.

8. The headphones of claim 6, wherein each of the first and second earphones comprises a buffer for caching the audio content received by the earphone prior to being played by the at least one acoustic transducer of the earphone.

9. The system of claim 8, wherein the processor circuits of the headphones are configured to receive firmware upgrades pushed from a remote network server.

10. The headphones of claim 9, wherein the processor circuit of each of the first and second earphones comprises:

- a digital signal processor that provides a sound quality enhancement for the audio content played by the at least one acoustic transducers of the earphone; and
- a baseband processor circuit that is in communication with the wireless communication circuit of the earphone.

11. The system of claim 1, wherein:

the mobile digital audio player is a first digital audio source;

the system further comprises a second digital audio player that is different from the first digital audio player; and the headphones transition to play digital audio content received wirelessly from the second digital audio source via a second wireless communication link based on, at least in part, a signal strength for the second wireless communication link.

12. The headphones of claim 11, wherein the processor circuits of the headphones are configured to receive firmware upgrades pushed from a remote network server.

20

13. The headphones of claim 12, wherein each of the first and second earphones comprises a buffer for caching the audio content received by the earphone prior to being played by the at least one acoustic transducer of the earphone.

14. The system of claim 1, wherein the processor circuits of the headphones are configured to receive firmware upgrades pushed from a remote network server.

15. The system of claim 1, wherein the processor circuit of the first earphone is configured to:

- process audible utterances by the user picked by the microphone in response to activation of the microphone by the user; and

transmit a communication based on the audible utterances via the Bluetooth wireless communication links.

16. The system of claim 1, wherein the rechargeable power source comprises a wirelessly chargeable circuit component.

17. The system of claim 1, wherein the rechargeable power source comprises a passive, wireless rechargeable power source.

18. The system of claim 1, wherein each of the first and second earphones comprises a buffer for caching the audio content received by the earphone prior to being played by the at least one acoustic transducer of the earphone.

19. The headphones of claim 1, wherein the processor circuit of each of the first and second earphones comprises a digital signal processor that provides a sound quality enhancement for the audio content played by the at least one acoustic transducers of the earphone.

20. The headphones of claim 19, wherein the processor circuit of each of the first and second earphones further comprises a baseband processor circuit that is in communication with the wireless communication circuit of the earphone.

* * * * *